







RAINSCAPES™

GARDEN WATERING KIT
KIT RIEGO DE JARDÍN
KIT ARROSAGE DU JARDIN

Parts List

A.		B.		C.		D.		E.		F.		A.	(50 ft.)	1/2 in. tubing
												B.	(5)	Adjustable nozzles with spikes
												C.	(10)	Risers
												D.	(5)	Half-circle nozzle adaptors
												E.	(8)	Tubing "goof" plugs
												F.	(5)	Hold down stakes

Installation & Operating Instructions

RainScapes Watering System™ is so easy to use, you might not even need this 7-step guide. But if you do, just follow this step-by-step.

Step 1: Roll out the tubing.

To avoid kinks in the tubing, place something heavy, such as a brick, on one end of the tubing and continue to roll out the remainder. Tip: Lay tubing in sun to keep from recoiling.

Step 2: Lay the tubing through the area you want watered.

It's not necessary, but you could draw yourself a map. Start by connecting the end of the tubing directly to your outdoor faucet or to a hose connected to the faucet. Next, lay the tubing through the area you want watered. Now, stand back and admire your progress.

Step 3: Placement of the spikes.

Grab a sprinkler from the box. They are the black spikes. Unscrew the cap from the spike by twisting the vertical grooves on the cap to the left. Repeat with remaining 4 sprinklers. Gently push the spikes into the ground at the places that you would like the sprinklers to be located. Place the tubing through the slot at the top of each spike. Your RainScapes Watering System™ nozzles have an adjustable spray distance of 1 foot to 12 feet so make sure you have placed each spike a minimum of 1 foot apart and no more than 12 feet. Note: You do not have to use all 5 of the sprinklers provided. Your system will work just as well with 3 or 4.

Step 4: Assemble the sprinklers.

With the tubing placed through each stake, screw the caps back onto the stakes, making sure that the plastic bar with the metal piercing unit fits into the slot on the stake. Do not over-tighten. It is not important which direction the metal piercing unit opening faces.

Step 5: Add hold-down stakes.

Hold-down stakes are included to help put unruly tubing in its place. Add stakes between nozzles or use in areas where it is difficult to "hide" your Simple Soaker. Push the stakes into the ground at a slight angle for the best staying power. Tip: Just cover the tubing with mulch or rock to blend into the landscape.

Step 6: Turn on the water.

Turn the water on slowly until the spray diameter has stopped increasing.

Step 7: Adjust the spray.

With just a couple of twists of your fingers, you can change the distance of the spray. So even if you are all thumbs, it's easy to adjust the nozzles just the way you want them. To adjust the distance of the spray, grip the top, larger, vertical grooves on the nozzle and rotate counter-clockwise to increase the distance and clockwise to decrease. Note: If water leaks from just below the nozzle, rotate the nozzle a couple of turns clockwise until the leaking stops.

HELPFUL HINTS: It's a "snap!"

The RainScapes Watering System™ was designed to put water where you want it. That's why we've included nozzle adaptors that change the full-circle spray to a half-circle. Simply "snap" them onto the very top of the nozzle and presto! HINT: the nozzle adaptor must be removed in order to adjust the spray or to unscrew a nozzle. Simply "unsnap" it!

Step 1 & 2



Step 3



Step 4



Step 5



Step 6 & 7



Step 7 & Adding Risers



Want to go higher?

If you need to water taller plants, you can raise the spray with the enclosed risers. Unscrew the nozzle from the cap, making sure to grip the lower, smaller, vertical grooves on the nozzle when unscrewing, and screw the riser onto the cap. Then screw the nozzle onto the top of the riser. You can even use more than one riser on each sprinkler for really tall plants. Just screw them together.

Having regrets about your piercings?

Need to move a sprinkler? No problem. We've included 8 "goof" plugs to patch your previous spots, or any goofs that happen along the way. Pinch the sides of the tubing and hold firmly when inserting a plug.

Tip: Need more than one system but only have one faucet? Eliminate the hassle of connecting and disconnecting multiple RainScapes Watering Systems™ and a hose by attaching a "Y" connector with shut-off valves (not included) to your faucet. See parts list below.

Care and maintenance of your RainScapes Watering System™.

To ensure that your RainScapes Watering System™ lasts as long as you do, once a year, remove nozzles and flush with water to remove debris. Before freezing weather, detach the tubing from the faucet, remove the end cap, and allow the water to drain from the system. It is not necessary to store this product indoors during colder months. The RainScapes Watering System™ was designed to be run at a lower water pressure. If you have high water pressure, do not run this system with the water completely on. If you are using a long garden hose to connect the RainScapes Watering System™, you may experience a decrease in water pressure and water flow.

CAUTION: Shock Hazard: Do not spray near electricity. Detach from faucet during freezing weather. This product intended for outdoor watering use only. Do not use with water exceeding 100°F (38°C) or with pressures exceeding 60 psi.

Additional Parts & Accessories Price List

Think your RainScapes Watering System™ can't get any better? Think again. You can customize your system with extra parts to make it the best it can be. Even if your dog ate your sprinkler, you're in luck. Plus, all of these parts will be delivered straight to your door. What more could you ask?

Risers



1. 50 ft. of 1/2 in. tubing



2. Spikes, caps and nozzles



3. Risers raise the spray




4. Nozzle adaptors + goof plugs



5. 1/2 in. tubing hold-down stakes



6. 1/2 in. tubing end plug kit



Item No.	Part No.	Description
1	77527	50 ft. of 1/2 in. tubing(metal swivel female coupling / plastic male coupling with plastic end cap)
2	77517	Spike, cap and nozzle assembly (5 per set)
3	77518	6 in. risers (5 per set)
4	77519	Nozzle adaptors (5 per set) + goof plugs (8 per set)
5	77528	Tubing hold-down stakes (5 per set)
6	77555	1/2 in. tubing end plug kit

Ordering information

Parts orders can be placed with:
 Consumer Service
 Robert Bosch Tool Corporation
 1-800-635-7668
 8:00 A.M. - 5:00 P.M. (CST) Mon. - Fri.
 www.lrnelson.com

